



QUEST

we drive you

material safety data sheet

Product Name:**AXEX HD 32**

Page 1/5

Version: 1

Date of issue:
2005/02/18MSDS No.:
Not availableDate of previous issue:
No Previous Validation

Label Requirements

Risk phrases: This product is not classified according to the EU regulations

1. Identification of the substance/preparation and of the company/undertaking

Product name : Axex HD 32
Product Code :
Use of the substance/preparation : Hydraulic anti-wear oil
Supplier : Quest Petroleum
P.O Box 35018
Newton Park
Port Elizabeth
6055

Emergency telephone number : 086 10 QUEST (SA Only)
+ 27 83 248 5116

2. Composition/information on ingredients

Substance Chemical characterization : Petrochemical

Ingredient name	CAS number	%	EC number	Classification
Base oils		> 90		Not classified
Alkyl phenol		< 0.2		N; R50/53
Zinc alkyldithiophosphate	68649-42-3	< 0.6	272-028-3	Xi; R38; R41; N; R51/53
See section 16 for the full text of the R Phrases declared above				

* Occupational Exposure Limit(s), if available, are listed in section 8

3. Hazard identification

The substance is not classified as dangerous according to Directive 67/548/EEC and its amendments.

Classification : Not classified
Physical/chemical hazards : No known significant effects or critical hazards
Human health hazards : Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation
Environmental hazards : No known significant effects or critical hazards

See section 11 for more detailed information on health effects and symptoms.

4. First aid measures

Inhalation : If inhaled, remove to fresh air.
Get medical attention if adverse health persist or are severe.

Ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear.

Skin contact : Remove contaminated clothing and shoes.
Wash contaminated skin with soap and water.
Get medical attention if irritation develops.

Eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Get medical attention if irritation develops.

See section 11 for more detailed information on health effects and symptoms.



QUEST

we drive you

material safety data sheet

Product Name:

AXEX HD 32

Page 1/5

Version: 1

Date of issue:
2005/02/18

MSDS No.:
Not available

Date of previous issue:
No Previous Validation

5. Fire-fighting measures

Extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemicals, or CO ₂ . Never direct a water jet in the container in order to prevent any splashing of the product which could cause spreading of the fire.
Special exposure hazard	:	No specific hazard.
Hazardous thermal decomposition products	:	These products are : carbon oxides (CO, CO ₂).
Special protective equipment for	:	Fire fighters should wear appropriate protective equipment and self-contained fire-fighters breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.
Remark	:	If fire can be controlled, cool container with water from unmanned hose holder or monitor nozzles until well after fire is out.

6. Accidental release measures

Personal precautions	:	Use suitable protective equipment (Section 8).
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods for cleaning up	:	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

7. Handling and Storage

Handling	:	Wash thoroughly after handling.
Storage	:	Keep container tightly closed. Keep container in a cool, well-ventilated area. Combustible materials should be stored away from extreme heat and away from strong oxidizing agent. Outside or detached storage is preferred.
<u>Packaging Materials</u> Recommended	:	Use original container. Empty container retain product residue and can be hazardous.

8. Exposure controls/personal protection

Ingredient name	Occupational exposure limits
Oil mist, mineral	ACGIH TLV (United States, 9/2004). Notes : Adopted Values enclosed are those for which changes are proposed. Consult the Notice of Intended Changes for current proposal. See Notice of Intended changes. STEL: 10mg/m ³ 15minute(s). Form: All forms TWA: 5mg/m ³ 8 hour(s). Form: All forms
Occupational exposure controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.



QUEST

we drive you

material safety data sheet

Product Name:**AXEX HD 32**

Page 1/5

Version: 1

Date of issue:
2005/02/18MSDS No.:
Not availableDate of previous issue:
No Previous Validation

Respiratory protection	:	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hand Protection:	:	Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Recommended	:	nitrile rubber, neoprene.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Skin protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

9. Physical and chemical properties

General Information

Appearance

Physical state	:	Liquid (Oily Liquid)
Colour	:	Yellow
Odour	:	Characteristic

Important health, safety and environment information

Flash Point	:	Closed cup:>190°C (374°F).
Relative density	:	0.88 (15°C / 59°F)
Solubility	:	Easily soluble in n-octanol. Insoluble in cold water, hot water.
Octanol/water partition coefficient	:	The product is more soluble in octanol; log (octanol/water) >6
Viscosity	:	32 mm/sec @ 40 C

Other information

Auto-ignition temperature	:	>250°C (482°F)
---------------------------	---	----------------

10. Stability and reactivity

Stability	:	The product is stable
Conditions to avoid	:	Avoid all possible sources of ignition (spark or flame). Avoid breathing vapors or spray mists.
Materials to avoid	:	Reactive with oxidizing agents.
Hazardous decomposition products	:	carbon oxides (CO, CO2)

11. Toxicological information

Potential acute health affects

Inhalation	:	Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation.
Ingestion	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Eye contact	:	No known significant effects or critical hazards.



QUEST

we drive you

material safety data sheet

Product Name:**AXEX HD 32**

Page 1/5

Version: 1

Date of issue:

2005/02/18

MSDS No.:

Not available

Date of previous issue:

No Previous Validation

Potential chronic health effects

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.
 Skin : No known significant effects or critical hazards.
 Target organs : Causes damage to the following organs: skin.
 Other adverse effects : Repeated exposure may cause skin oil blisters.

12. Ecological information

Remarks : Product is not hazardous to water. Not expected to bioaccumulate.
 Inherently biodegradable

13. Disposal considerations

Methods of disposal : Non-hazardous waste
 Recycle, if possible
 The generation of waste should be avoided or minimized wherever possible. Disposal of this products, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

14. Transport information

Regulatory information	UN Number	Proper Shipping name	Class	Packing Group	Label	Additional information
ADR/SABS 0228 Class	Not Regulated	-	-	-	-	-
IMDG Class	Not Regulated	-	-	-	-	-
IATA Class	Not Regulated	-	-	-	-	-

15. Regulatory information**SABS 0263 / EU Regulations**

Risk phrases : This product is not classified according to the EU regulations.

Product use : Classification and labeling have been performed according to EU directives 67/548/EEC, 1999/45/EC including amendments and the intended use.
 - Industrial applications



QUEST

we drive you

material safety data sheet

Product Name:

AXEX HD 32

Page 1/5

Version: 1

Date of issue:
2005/02/18

MSDS No.:
Not available

Date of previous issue:
No Previous Validation

16. Other information

Full text of R phrases referred to in
Sections 2 and 3 – Europe

: R38 – Irritating to skin
R41 – Risk of serious damage to eyes.
R51/R53 – Toxic to aquatic organisms, may cause
long-term adverse effects in the aquatic
environment.

Prepared by

: Quest Petroleum Technical Department

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named suppliers nor any of its subsidiaries assumes any liability for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user.

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.